



Phone: 416.690.1690 or 1.800.567.8481
Email: info@videolink.ca
Website: www.videolink.ca

Video Formats

- (HD) 1080p 23.98, 25, 29.97, 50, 59.94
- (HD) 1080i 25, 29.97
- (HD) 720p 50, 59.94
- (SD) 525i, 625i

Video Input

- 1 x HDMI Standard Type A connector
- HDMI v1.4a, RGB or YCbCr

Video Output

- 1 x HDMI Standard Type A connector
- HDMI v1.4a, RGB or YCbCr

Audio Digital

- 2-Channel, 24-bit HDMI embedded audio, 48 kHz sample rate, synchronous

Audio Analog

- 2-Channel, 24-bit HDMI embedded audio, 48 kHz sample rate, synchronous

Video Codec Support

- Realtime, ultra-low latency, full-bitrate NDI (i-frame)

Display

- Bicolor Tally (Red/Green)
- Multicolour status information
- Full status information on HDMI output (Selectable)

Network Interface

- 10/100/1000 Ethernet (RJ-45) with PoE (Power over Ethernet)
- Embedded web configuration panel for control and firmware updates

User Interface Controls

- Network settings
- Video settings
- Tally settings
- Audio and Comms settings

Size (w x d x h)

- 98x110x22mm

Weight

- 200g

Power

- 100-240V, 50/60 Hz Universal Input, +5-18V DC7W Max
- Power over Ethernet (PoE) 802.3af/at

Phone: 416.690.1690 or 1.800.567.8481
Email: info@videolink.ca
Website: www.videolink.ca