



Phone: 416.690.1690
 Toll Free: 1.800.567.8481
 Email: info@videolink.ca
 Website: www.videolink.ca

NewTek Connect Spark™ Pro

Technical
Specifications



Connect Spark™ Pro Tech Specs

Video Input	1 x HDMI 2.0
Audio Input	1 x HDMI embedded audio input (48/44.1/32 KHz) 1 x 1/4" (6.35 mm) Line Level (48 KHz) Stereo audio (2-channel LPCM)
Encoding	NDI®
Networking	1 x RJ-45 port for Gigabit Ethernet networking
Interface	Web-based user interface for configuration and monitoring
Tally	Tally support via NDI® or 1/8" audio jack Built-in program/preview tally lights
Formats	2160p: 60, 59.94, 50 1080p: 60, 59.94, 50, 30, 29.97, 25, 24 720p: 60, 59.94, 50, 29.97, 25, 24 576p: 50 (16:9, 4:3) 480p: 60, 59.94 (16:9, 4:3)
Power	Power over Ethernet (POE) External power via USB type-C (5V 2A)
Environmental	Operating temperature: -20°C to 80°C Relative humidity: 20% to 90%
Physical	Portable enclosure with threaded screw camera mount <ul style="list-style-type: none"> • 5.37 x 3.32 x .92 in (136.40 x 84.33 x 23.37 mm) • .65 lbs (.28 kg)

Subject to change without notice.



\$995 US - Contact Us

Phone: 416.690.1690
 Toll Free: 1.800.567.8481
 Email: info@videolink.ca
 Website: www.videolink.ca